



- Inlet: Ø350
- +1 Ø250
 - +2 Ø250
 - +3 Ø250
 - +4 Ø250
 - 4 Ø250

Förderrichtung Conveying direction sans de manutention		
F ₂	←	F ₁
Verlagerungspunkte Supporting points		
F ₂	←	F ₁
Points de support		
Mindestabstand zu stationären Teilen 80 mm Minimum distance to stationary parts 80 mm Distance minimum aux éléments stationnaires 80 mm		
Betriebsbelastung Operation load Charge en service		
	stat. (N)	dyn. (N)
F ₁	v	4545 N ± 190 N
	h	± 20 N
F ₂	v	4545 N ± 135 N
	h	± 20 N
Frequenz, Frequency, Frequence 24 Hz		
Gewicht, Weight, Poids ~ 1670 kg		
1kp = 9,81 N 1N = 0,102 kp		

index	modification	date	name	index	modification	date	name
material							
weight (kg)		scale		date		name	
1332		1:20					
drawn		checked		date		name	
description		reference		description		reference	
		MSizer compact, C154x General drawing, for quotation only					
tolerances ISO 2768-mK ISO 13920 BE EN 20273-m		part-no.		drawing-no.		page / of 1 / 1	
This drawing is not allowable for neither duplication nor accessible for any third party or competitor without our permission.							

ALLGAIER | PROCESS TECHNOLOGY
 Fredrik Mogensen AB
 Sveavägen 26
 544 50 Hjo / Sweden
 www.allgaier-process-technology.com/en/fredrik-mogensen-ab