

MOGENSEN-SEL - an efficient and compact solution



- *Mogensen-SEL with dual motor.*



- *Modularised 0,5 m wide rear covers with 2 quick-release fasteners*



- *Screen cloth tensioning with electronic remote supervision*



- *Frame with vibration-dampening springs*



- *Strategically positioned inspection ports simplify screen cloth change*



The Mogensen-SEL is an efficient, compact and flexible Sizer with extremely high capacity. The SEL-model's linear vibration movement enables careful, efficient screening. The modular construction allows simple, cost-effective process adaptation. The Mogensen-SEL is supplied on a support frame which simplifies transportation, installation and start-up. The well thought-out construction minimizes down time for service and screen cloth change, partly thanks to dust covers

The Mogensen-SEL is a tried and tested construction that gives the best possible operational reliability even under extreme conditions.

The Mogensen-SEL is primarily intended for separating sizes from 0.1-30 mm, and can handle input dimensions up to around 50 mm. It can be supplied in widths of 1, 1.5 and 2 m, with three to five screening decks


A flexible range of Sizers

The standard equipment includes an integrated feeder unit with adjustable spreader, which often eliminates the need for a separate feeder. The equipment can be made with outlets designed for round or rectangular connections. The Sizer is meticulously tested prior to delivery, to guarantee function and quality.

The Mogensen-SEL has a complete accessory program with for example: an electrical control system for easy handling and reliable operation, electronic supervision of the screen cloth tensioning and various systems for wear protection and screen cloth cleaning.



At Mogensen, we can help customers verify potential screening solutions in our test center.



- Large capacity
- High screening efficiency
- Compact and lightweight
- Low power requirement
- Robust and operationally reliable construction
- Wide range of accessories
- Maintenance-friendly
- Modular design
- Simple operation

Machine type
Interior width, machine (dm)
No. of decks
No. vibrator poles

SEL 1536

Type	Width	Length	Height
SEL 1036	1440	3250	2050
SEL 1046	1440	3350	2300
SEL 1056	1440	3650	2550
SEL 1536	1935	3350	2150
SEL 1546	1935	3450	2400
SEL1556	1935	3750	2650
SEL 2036	2450	3650	2400
SEL 2046	2450	3800	2650
SEL 2056	2450	4100	2900

